



**Approvals and conformities**

QPL-AMS 2644

**MANUFACTURER:** SHERWIN (USA) / NDT Europa (NL)

**DESCRIPTION / APPLICATION(S):**

Powerful volatile solvent, able to move water away from discontinuities.

**Companion products:** all penetrants

***DIRECTIONS FOR USE***

---

To clean a part, apply DR-62 plentifully and wipe simultaneously with a clean, dry rag. DR-62 quickly evaporates and leaves the part completely clean and without any trace of lubricant, grease or oil.

***TECHNICAL CHARACTERISTICS***

---

Very low halogen and sulfur content.

Compatible with all metals, ceramics, and certain plastics.

Appearance . . . . . colorless liquid

Flash point . . . . . < 0°C

***PRECAUTIONS FOR USE AND STORAGE***

---

**Transport / Handling:** Refer to Material Safety Data Sheet (MSDS).

**Storage :** Keep away from moisture

Temperature range: 0°C à 50°C

Keep packaging closed after taking out some of the product.

1 Date : 04-07-2017 Written and checked by : F. Héron

**This technical data sheet replaces and cancels the previous one.**

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.

1 Date : 04-07-2017 Written and checked by : F. Héron