

Approvals and conformities

ASME

MANUFACTURER: NDT-Italiana (I)

DESCRIPTION / APPLICATION(S):

UHT is a silicon gel with additives. It may be used for Ultrasonic Testing from 200°C to 550°C.

This product does not flow, does not dry, does not stick and enables a very good acoustic transmission

Companion products: /

DIRECTIONS FOR USE

Apply the product on the area to be controlled.

Use the UT equipment as specified by the manufacturer.

The signal may be attenuated if the product is used below 200°C.

TECHNICAL CHARACTERISTICS

Very low halogen and sulfur content.

Compatible with all metals

Appearance white paste

Flash point > 400°C

PRECAUTIONS FOR USE AND STORAGE

Transport / Handling: Refer to Material Safety Data Sheet (MSDS).

Storage : Keep away from moisture

Temperature range: 0°C à 50°C

Keep packaging closed after taking out some of the product.

1 Date : 06-07-2017 Written and checked by : F. Héron

This technical data sheet replaces and cancels the previous one.

1 Date : 06-07-2017 Written and checked by : F. Héron

babbco
socomore NDT

T. +33 (0)1 30 80 81 82 - F. +33 (0)1 30 80 81 99
ZI des Ebisoires - BP 136 - 15 rue des Frères Lumière - 78374 Plaisir cedex - France
www.babbco.fr - www.sherwinbabbco.eu

SHERWIN
babbco