

ACTIVE CHARCOAL CA 30**MANUFACTURER : Babb Co (FR)****DESCRIPTION / APPLICATION(S) :**

ACTIVE CHARCOAL in granular prepared from coal, peat, etc..., activated with steam at high temperature.

The coal is particularly recommended for any process in liquid phase treatment and discoloration of water from penetrant testing.

Companion products : /

SPECIFICATION(S) / STANDARD(S) :

- Conforms to specification(s) : « Food Chemicals Codex »

PHYSICO-CHEMICAL PROPERTIES:

- Iodine index : > 920 mg/g
- Granulometry : > n°8 (2,38 mm) : 15 % max.
: < n°30 (0,59 mm) : 4 % max.
- Volume of pores : 0,85 cm³/g

INSTRUCTIONS :

Wet carefully the active charcoal (approximately 48h) in order to avoid loss of charcoal (still floating) during the initial washing against current.

Rinse then the burden of activated charcoal against a current in order to eliminate dust. The clean water is then sent on activated charcoal from top to bottom at a speed of approximately 10 m/h.

To achieve peak performance, it is necessary to depack the column of activated carbon CA 30 regularly against the current. You can consult us for the implementation. Frequency suggested: every month at least.

HEALTH AND SAFETY : Refer to Material Safety Data Sheet (MSDS).

The information given herein is given in good faith to our customers for the sole purpose of assisting them in the use of the products. The document contains no formal or implicit guarantee regarding its use.

Babb Co cannot be held responsible for damages of any nature resulting from information provided in this document. In addition, none of the information which the document contains should be interpreted as a recommendation for the use of the products which would infringe the protected rights of industrial property.